



Part I:

Pos. 1.1 Pillar candles press (diameter min. 40mm, max. 80mm; height min. 40mm max 80mm; capacity 1500 pcs/hour; 12 stamps)

Part II:

Pos. 2.1 Robot

Pos. 2.2 Robot fence

Pos. 2.3 Robot tool (to grab 12 pcs during one cycle, tool cannot cause candle damages)

Pos. 3 Conveyor (dimension B x L x H 3300 x 19 000 x 950mm; mesh; adjustable speed in reference to the candles diameter)

Pos. 4.1 Robot

Pos. 4.2 Robot fence

Pos. 4.3 Robot tool (to grab 12 pcs during one cycle, tool cannot cause candle damages)

Part III:

Pos. 5 Wick inserting device

Part IV:

Pos. 6.1 Temp. stabilization tunnel (incoming candles temp. min. 20°C max. 80°C, decreasing temp. by 15-20°C)

Pos. 6.2 Temp. stabilization tunnel (with air temp. min. 5°C max. 30°C)

RYSOWAŁ:	Marcin Huryski	Nazwa:	Eko 6 line	DZIAŁ TECHNICZNY
SPRAWDZIŁ:	Marcin Huryski	Nr. rysunku:	NT/150913.01	
ZATWIERDZIŁ:	Marcin Huryski	Skala:		Format:
UWAGI:				A4